



FCS-3098 Version: 1-TH

Zoom Dome IP Network Camera, 8-Megapixel, H.265, 4.3X Optical Zoom, 802.3af PoE, IR LEDs, two-way audio, Indoor/Outdoor, Vandalproof

The LevelOne FCS-3098 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP67 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3098 offers 8-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- 8-Megapixel high-definition resolution
 - Video compression: H.264, H.265, MJPEG
 - Supports 4.3X optical zoom
 - Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
 - Vandal-proof IK10-rated housing
 - Weatherproof IP67-rated housing
 - Built-in infrared LEDs for night viewing up to 30m
 - Built-in Micro SDHC/SDXC card slot for local storage
 - Dual power support: 12V DC/PoE (IEEE 802.3af)
 - Free surveillance and CMS (Central Management System) software packages with 64-channel license
-

Specifications

System Specifications

Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv4, IPv6, ANR

Image Sensor:

1/2.5" Progressive Scan CMOS

Lens:

2.8~12mm motorized VF lens, F2.0

Port:

1 x RJ-45 10/100 Mbps Base-T PoE port

Power Connector

Audio: In/Out

1Vp-p composite output (75 Ω/BNC)

I/O terminal block (1 DI/1 DO)

1 x MicroSD XC/HC card slot

**Button/Knob:**

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

IR LEDs for illumination up to 30m

Shutter Time:

1/3 ~ 1/100,000 sec

Angle of View:

Horizontal field of view: 115° to 35°

Vertical field of view: 60° to 19°

Diagonal field of view: 146° to 38.5°

Video Compression:

H.265, H.264, MJPEG

Resolution:

50Hz: 20 fps (3840 × 2160), 25 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

Output Video Format:

AVI

Audio Compression:

G722.1/G711ulaw/G711alaw/G726/MP2L2

Power Input:

12 VDC, 0.95A, max. 11.5W

PoE (802.3af, 37V to 57V), 0.3A to 0.1A, max. 12.9W

Power Consumption:

11.5-12.9W

Data Rate:

Video Bit Rate: 32 Kbps to 16 Mbps

Audio Bit Rate: 32 to 128kbps

Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

Optical Zoom:

4.3X Optical Zoom

Features

General:

Rotate mode, Brightness, Contrast, Saturation, and Sharpness are adjustable via web browser, Motion Detection, Digital Noise Reduction, ROI

PoE:

PoE(802.3af, class 3)

Security:

One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, 5 x zoom Privacy Mask, Watermark, IP Address Filter

Management:

Behavior Analysis: Line crossing detection, intrusion detection, unattended baggage detection, object removal detection

Line Crossing Detection: Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported

Intrusion Detection: Enter and loiter in a pre-defined virtual region, up to 1 pre-defined virtual regions supported

Object Removal Detection: Objects removed from the pre-defined region, such as the exhibits on display.

Unattended Baggage Detection: Objects left over in the pre-defined region such as the baggage, pure dangerous materials

Face Detection: Human face appears in the image can be detected and trigger linkage method.

Video:

120dB Wide Dynamic Range

Region of Interest: Support 1 fixed region for mainstream and sub stream separately
support Triple stream

Audio:

1 audio input (line in), 1 audio output

Performance

Number of Clients:

32

Frame Rate (fps):

50Hz: 20 fps (3840 × 2160), 25 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

Minimum illumination:

Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR

Environment

Operating Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Operating Humidity (Non-condensing):

Humidity 95% or less

Physical Specifications

Dimensions (W x D x H mm):

153.4 × 153.4 × 133.1 mm (6.04" × 5.24")

Weight (g):

1287

Color:

White

Approval and Compliance

EMI/EMS:

CE, FCC, uL

Safety:

IK10

Environmental Test:

IP67

Others:

ONVIF, ISO-9001/ISO-14001 certified factory

Others

Supported Browsers:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Order Information

FCS-3098



Package Contents

FCS-3098
Resource CD (User Manual, Utility, 64-CH Monitoring Software)
Screw Kit

Optional Accessory



CAS-7342
Pendant Mount Bracket



CAS-7343
Wall Mount Bracket



CAS-7344
Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7345
Corner Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.